X 6' I.D. ELECTRICAL MANHOL NOT TO SCALE: ALL DIMENSIONS ARE SUBJECT TO ALLOWABLE SPECIFICATION TOLERANCES MATERIALS & FEATURES CONCRETE: 5,000 PSI, 28 DAY STRENGTH. REINFORCING: ASTM A-615, GRADE 60 LOADING: DESIGNED FOR H20 LOADING 84" C.I. CASTINGS: ASTM A48, CLASS 30/35 GROUND ROD OPENING (IN FLOOR) 36" O ACCESS OPENING IN SLAB TOP SUMP IN FLOOR 84" 72" RECESSED PULLING IRON (TYPICAL OF 4 IN FLOOR) 6" \$ TERMINATOR (TYPICAL) LOCATION AS REQUIRED 6" В PLAN VIEW 36" o ACCESS **OPENING** 6" 6" O TERMINATOR (TYPICAL) LOCATION AS REQUIRED -"Ò" SUMP RECESSED PULLING IRON (TYPICAL OF 4) SECTION AA **ELEVATION BB** 6' X 6' ID ELECTRICAL MANHOLE Capital Concrete Products FILE LOC. ELECTRIC MANHOLE/ 6X6 ID ELECTRIC MANHOLE 5264 Hwy. 71 East • Del Valle, Texas 78617 DATE: SUSAN MENTA OCTOBER 14, 2009